



AIRCRAFT ACCESS STAND

DESCRIPTION

The Aircraft Access Stand is designed for access to the main fuselage doors. The 8" / 20.3cm castors allow for easy manoeuvring in minimal space. The design allows for use in hangar areas as well as line maintenance and ramp applications.

Our Professional Engineers can design custom models based on your specific requirements.

WHAT OUR CUSTOMERS ARE SAYING

"We would highly recommend this product to any company completing regular maintenance on commercial aircraft. We find that Liftsafe Fall Protection is more than willing to work with us in creating safe, economical and multi-purpose designed equipment, tailored to our needs."



NATO N/CAGE CODE: L03Y4



member of

NBAA



PRODUCT FEATURES

- 8" / 20.3cm split castor with brake and swivel lock
- Custom colour finish
- Tow bar
- Fail-safe hydraulic cylinder locks
- Split wheel castors for easy movement
- Designed and tested in accordance with ANSI-ASC A14.7 and BS EN 131.7, DIN EN 12312-8, EN 1915-1, and includes CE Certification

BENEFITS

- Designed for minimal footprint
- Easy mobility ensuring the stand can be relocated quickly
- Designed for use in hangar areas as well as line maintenance and ramp applications
- Customizable to individual operational requirements
- 2 year limited warranty on components
- 10 year limited warranty on structure



AIRCRAFT ACCESS STAND

AVAILABLE ACCESSORIES

- Air powered pump
- Utilities package
- Fall restraint anchor points



TECHNICAL SPECIFICATIONS

MODEL NO.	DF101579-01	DF101580-02
DESIGNED FOR	Aircraft Entry Access – Adjustable Height	Aircraft Entry Access – Fixed Height
AIRCRAFT TYPE	Based Upon Customer Requirements	Based Upon Customer Requirements
MOVEMENT	3 Persons	2 Persons
TOWING SPEED	6 MPH / 10 KPH	6 MPH / 10 KPH
FOOTPRINT	Based Upon Customer Requirements	Based Upon Customer Requirements
SHIPPING (DIMS)	Based Upon Customer Requirements	Based Upon Customer Requirements
WEIGHT CAPACITY	Based Upon Customer Requirements	Based Upon Customer Requirements
CERTIFICATIONS	ANSI-ASC A14.7, BS EN 131.7, CE, DIN EN 12312-8 & EN 1915-1	
MATERIAL	Steps: Aluminum Frame: Steel	Steps: Aluminum Frame: Steel
FINISH	Custom Colour	Custom Colour
CASTOR DETAILS	8" / 20.3cm Split Castor with Brake and Swivel Lock	8" / 20.3cm Split Castor with Brake and Swivel Lock
CONTROLS	Manual Foot Pump	N/A
FALL RESTRAINT ANCHOR POINTS	Not Required	Not Required
PADDING MATERIAL	Equipped	Equipped